# S-38.3192
# **Exercise Session:**
# MPLS/BGP L3 VPN

# 15.2.2008

# Motivation

```
system {
    host-name cabernet;
    backup-router 10.11.0.254;
    time-zone Europe/Helsinki;
    root-authentication {
        encrypted-password "$1$S1IzjTvT$iNFojsaEdT1GyokBKsIDY1";
## SECRET-DATA
    }
    services {
        ftp;
        ssh {
            root-login deny;
        }
        telnet;
    }
    ntp {
        inactive: server 10.255.0.50 version 4;
        inactive: server 10.255.0.51 version 4;
        server 10.255.16.41 version 2;
    }
}
logical-routers {
    merlot {
        interfaces {
            lt-1/2/0 {
                unit 1 {
                    encapsulation ethernet;
                    peer-unit 0;
                    family inet {
                        mtu 1700;
                        address 10.111.0.25/30;
                    }
                    family iso;
                    family mpls;
                }
                unit 2 {
                    encapsulation ethernet;
                    peer-unit 3;
                    family inet {
                        mtu 1700;
                        address 10.111.0.13/30;
                    }
                    family iso;
                    family mpls;
                }
            }
            ge-1/3/0 {
                unit 2 {
                    vlan-id 2;
                    family inet {
                        mtu 1700;
                        address 10.111.0.10/30;
                    }
                    family iso;
                    family mpls;
                }
            }
            lo0 {
                unit 4 {
                    family inet {
                        address 10.100.100.4/32 {
                            primary;
                        }
                    }
                    family iso {
                        address 49.0001.0102.4124.8004.00;
                    }
                }
            }
        }
        protocols {
            rsvp {
                interface lt-1/2/0.1 {
                    aggregate;
                    link-protection;
                }
                interface lt-1/2/0.2 {
                    aggregate;
                    link-protection;
```

```
                }
            interface ge-1/3/0.2 {
                aggregate;
                link-protection;
            }
        }
        mpls {
            label-switched-path mer-to-cab {
                from 10.100.100.4;
                to 10.100.100.6;
                ldp-tunneling;
                link-protection;
            }
            label-switched-path mer-to-sau {
                from 10.100.100.4;
                to 10.100.100.2;
                ldp-tunneling;
                link-protection;
            }
            label-switched-path mer-to-pin {
                from 10.100.100.4;
                to 10.100.100.3;
                ldp-tunneling;
                link-protection;
            }
            interface lt-1/2/0.2;
            interface ge-1/3/0.2;
            interface lt-1/2/0.1;
        }
        isis {
            reference-bandwidth 100g;
            spf-delay 150;
            no-ipv6-routing;
            level 1 disable;
            level 2 wide-metrics-only;
            interface lt-1/2/0.1 {
                point-to-point;
            }
            interface lt-1/2/0.2 {
                point-to-point;
            }
            interface ge-1/3/0.2 {
                point-to-point;
            }
            interface lo0.4;
        }
        ldp {
            interface lo0.4;
            session 10.100.100.1 {
                authentication-key "$9$tURx0BE7NbaZjrevL7N2g"; ##
SECRET-DATA
            }
            session 10.100.100.2 {
                authentication-key "$9$MH7Lxdji.FnCYgoGji5T"; ##
SECRET-DATA
            }
            session 10.100.100.3 {
                authentication-key "$9$uBR5BIc-dsZUHevWx-d4o"; ##
SECRET-DATA
            }
            session 10.100.100.5 {
                authentication-key "$9$NSVwgPfzApBZUjqPf6/"; ##
SECRET-DATA
            }
            session 10.100.100.6 {
                authentication-key "$9$A/Z/uORx7VoJDyIK8x7Y2"; ##
SECRET-DATA
            }
        }
        routing-options {
            router-id 10.100.100.4;
        }
    }
    pinot_noir {
        interfaces {
            lt-1/2/0 {
                unit 3 {
                    encapsulation ethernet;
```

```
            peer-unit 2;
            family inet {
                mtu 1700;
                address 10.111.0.14/30;
            }
            family iso;
            family mpls;
        }
    }
    ge-1/3/0 {
        unit 1 {
            vlan-id 1;
            family inet {
                mtu 1700;
                address 10.111.0.6/30;
            }
            family iso;
            family mpls;
        }
    }
    lo0 {
        unit 3 {
            family inet {
                address 10.100.100.3/32 {
                    primary;
                }
            }
            family iso {
                address 49.0001.0102.4124.8003.00;
            }
        }
    }
}
protocols {
    rsvp {
        interface ge-1/3/0.1 {
            aggregate;
            link-protection;
        }
        interface lt-1/2/0.3 {
            aggregate;
            link-protection;
        }
    }
    mpls {
        label-switched-path pin-to-mer {
            from 10.100.100.3;
            to 10.100.100.4;
            ldp-tunneling;
            link-protection;
        }
        label-switched-path pin-to-cha {
            from 10.100.100.3;
            to 10.100.100.1;
            ldp-tunneling;
            link-protection;
        }
        interface ge-1/3/0.1;
        interface lt-1/2/0.3;
    }
    isis {
        reference-bandwidth 100g;
        spf-delay 150;
        no-ipv6-routing;
        level 1 disable;
        level 2 wide-metrics-only;
        interface lt-1/2/0.3 {
            point-to-point;
        }
        interface ge-1/3/0.1 {
            point-to-point;
        }
        interface lo0.3;
    }
    ldp {
        interface lo0.3;
        session 10.100.100.1 {
            authentication-key "$9$9/Xstu1LX-goGcyIMLXws"; ##
SECRET-DATA
```

```
        }
        session 10.100.100.2 {
            authentication-key "$9$Q7Pq36AIeWdb2O1RSIex7"; ##
SECRET-DATA
        }
        session 10.100.100.4 {
            authentication-key "$9$AN1iuORx7VoJDyIK8x7Y2"; ##
SECRET-DATA
        }
        session 10.100.100.5 {
            authentication-key "$9$OGtTIEyVb2UjqvWLNVbaJ"; ##
SECRET-DATA
        }
        session 10.100.100.6 {
            authentication-key "$9$2SoJDn6AIEyqmfzn60O"; ##
SECRET-DATA
        }
    }
    routing-options {
        router-id 10.100.100.3;
    }
}
shiraz {
    interfaces {
        fe-0/0/1 {
            unit 0 {
                family inet {
                    address 10.111.0.38/30;
                }
            }
        }
        lo0 {
            unit 8 {
                family inet {
                    address 10.100.100.8/32 {
                        primary;
                    }
                }
            }
        }
    }
    protocols {
        bgp {
            export export;
            group vpn-red {
                type external;
                peer-as 65000;
                neighbor 10.111.0.37 {
                    family inet {
                        unicast;
                    }
                }
            }
        }
        policy-options {
            policy-statement export {
                term 1 {
                    from protocol direct;
                    then accept;
                }
                term 2 {
                    then reject;
                }
            }
        }
        routing-options {
            router-id 10.100.100.8;
            autonomous-system 65002;
        }
    }
}
interfaces {
    fe-0/0/0 {
        unit 0 {
            family inet {
                address 10.111.0.37/30;
            }
```

15.2.2008  S-38.3192 Exercise session:
MPLS/BGP L3 VPN

# Network Configuration

S-38.3192 Exercise session:
MPLS/BGP L3 VPN

# To-do list

- Create VRFs

  – Assign the VRFs to PE-CE interfaces

- Change MPLS TE parameters

- Set up BGP sessions

  – Set up neighborhoods

  – Configure Address family parameters

- Test the network

  – Use a ping flow from CE to CE (LB0<->LB0)

# Today's topic: MPLS/BGP L3 VPN

- Do the exercise. You find it at course's website.
- Send the exercise as an email attachment to ttheikk2@netlab.tkk.fi. File type must be PDF.
- Remember the feedback questions
- Next exercise session will be on Fri 22.2. at 12 -14 o'clock in Maari-A, BGP/VPN Help Session

# For the Next Exercise Session

- Topic will be Network failures
- Familiarize yourself with the topic
- Next (new topic) exercise session will be on Fri 29.2.2008 at 12 -14 o'clock in Maari-A